

home of the **microsave**[®] cavity liner

NE-1878BPQ

PROFESSIONAL INVERTER MICROWAVE

Equipped with Panasonic's unique Inverter technology, which enables faster, more even, gentler cooking. It also uses less energy and the all-metal door design ensures easy cleaning, extending the lifespan of the microwave.



Panasonic



Panasonic



INVERTER

EVEN HEATING

Inverter technology allows you to cook, reheat or defrost your food without creating cold spots or overcooking edges. This Inverter microwave delivers an accurate power level; when you ask for 60% power, the oven delivers 60% power for the entire duration of the cooking time chosen. This applies no matter what power level is selected giving you better, more even cooking results.

ENERGY SAVING

With Inverter microwaves, you can save up to 6.3% on energy consumption*, which is good for the environment, and your wallet.

* Compared to NE-1853 (2650W Inverter microwave compared to 2830W LC type microwave).



LIGHTER & SMALLER

Inverter microwaves are equipped with a compact and efficient power supply that weights only 500g. This makes the overall unit lighter, more portable and easier to move around for cleaning, as the total unit weight is brought down to approx. 12kg (40% less compared to NE-1853).



30.0kg
NE-1853BPQ

17.5kg
NE-1878BPQ



Panasonic

METAL DOOR DESIGN

The world's first all-metal door professional microwave with Inverter technology. An innovative design, specifically intended for the UK market. A full-metal door microwave that looks like a conventional oven. It adapts to every environment and you can even install it in your open kitchen. Most importantly the inside of the metal door has no ridges, seals or film to clean around, it's totally smooth. This makes the inside of the unit very easy to clean and increases the lifespan of the oven.



SPLATTER SHIELD DETECTION

The NE-1878 has been programmed to not operate when the ceiling plate is not in place.

Also available from Regale is the Panasonic authorized Microsave CPS3A Cavity Liner. The Cavity Liner protects the microwave's interior base, ceiling plate and the lens light cover and is dishwasher safe, making cleaning at the end of service, a breeze.



Power Source	50Hz, single phase 230-240 V	
Required Power	11.6A 2650 W	
Output*	HIGH	P10: 1800 W*
	MEDIUM HIGH	P9: 90% P8: 80% P7: 70% P6: 60%
	MEDIUM	P5: 50% P4: 40%
	LOW	P3: 30% P2: 25%
	DEFROST	P1: 340 W
	OFF	P0: 0%
	HEAT FROM TOP DOWN	PU1: 50% PU2: 25%
	HEAT FROM BOTTOM	PL1: 50% PL2: 25%
Frequency MHz	2450 MHz	
Outer Dimensions (wxdxh)	422 mm x 476mm x 337mm	
Cavity Dimensions (wxdxh)	330 mm x 310mm x 175mm	
Net Weight	17.5 kg	
Timer	Maximum programmable time for single stage heating P1 and P0=30 minutes P10-P2, PU1-PL2=15 minutes	
Note	* IEC Test Procedure. Specifications subject to change without notice	

Space Saving Design

Stackable unit

Inverter Technology

Faster, more even & gentler cooking

Metal Door Design

Elegant, durable & easy maintenance door

